



# Material Safety Data Sheet

Sikafloor 130 Part H

## 1. Product and company identification

**Product name** : Sikafloor 130 Part H  
**Supplier** : Sika Corporation, Construction  
201 Polito Avenue  
Lyndhurst, NJ 07071  
www.sikaconstruction.com  
**Telephone no.** : (201) 933 - 8800  
**Fax no.** : (201) 804 - 1076  
**In case of emergency** : CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887  
**Manufacturer** : Sika Corporation, Operations  
201 Polito Avenue  
Lyndhurst, NJ 07071  
www.sikacorp.com  
**Telephone no.** : (201) 933 - 8800  
**Validation date** : **8. October 2008.**  
**Print date** : 8. October 2008.  
**Product type** : Amine

## 2. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Mixed Cycloaliphatic Amines	Mixture	60 - 100
benzyl alcohol	100-51-6	5 - 20

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 3. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### Potential acute health effects

**Inhalation** : Irritating to respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.  
**Ingestion** : Harmful if swallowed. Corrosive to the digestive tract. Causes severe burns.  
**Skin** : Severely corrosive to the skin. Causes severe burns. Harmful in contact with skin. May cause sensitization by skin contact.  
**Eyes** : Corrosive to eyes. Causes burns.

See toxicological information (section 11)

## 4. First aid measures

**Eye contact** : Get medical attention immediately. Immediately flush eyes with plenty of water for at least 15 minutes. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician.  
**Skin contact** : No known significant effects or critical hazards.

## 4 . First aid measures

- Inhalation** : Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Maintain an open airway. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

## 5 . Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8 . Exposure controls/personal protection

**Product name**

benzyl alcohol

**Exposure limits**

**AIHA WEEL (United States, 1/2007).**

TWA: 10 ppm 8 hour(s).

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 9 . Physical and chemical properties

<b>Physical state</b>	: Fluid.
<b>Flash point</b>	: Closed cup: 101°C (213.8°F)
<b>Color</b>	: Amber.
<b>Odor</b>	: Amine-like.
<b>Boiling/condensation point</b>	: >147°C (>296.6°F)
<b>Density</b>	: ~1.03 g/cm <sup>3</sup> [20°C (68°F)]

## 10 . Stability and reactivity

<b>Stability</b>	: The product is stable.
<b>Conditions to avoid</b>	: No specific data.
<b>Materials to avoid</b>	: No specific data.
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
<b>Hazardous polymerization</b>	: Under normal conditions of storage and use, hazardous polymerization will not occur.

## 11 . Toxicological information

### Potential chronic health effects

<b>Chronic effects</b>	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
------------------------	---

### Acute toxicity

<b>Conclusion/Summary</b>	: Not available.
---------------------------	------------------

## 12 . Ecological information

<b>Environmental effects</b>	: No known significant effects or critical hazards.
------------------------------	---

## 13 . Disposal considerations

<b>Waste disposal</b>	: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
-----------------------	---

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Additional information
<b>DOT Classification</b>	UN3066	Paint	8	III	-
<b>TDG Classification</b>	UN3066	Paint	8	III	-
<b>ADR/RID Class</b>	UN3066	Paint	8	III	-

## 14 . Transport information

<b>IMDG Class</b>	UN3066	Paint	8	III	<b>Emergency schedules (EmS)</b> F-A, S-B
<b>IATA-DGR Class</b>	UN3066	Paint	8	III	-

PG\* : Packing group

## 15 . Regulatory information

- U.S. Federal regulations** :
- United States inventory (TSCA 8b):** All components are listed or exempted.
  - SARA 302/304/311/312 extremely hazardous substances:** No products were found.
  - SARA 302/304 emergency planning and notification:** No products were found.
  - SARA 302/304/311/312 hazardous chemicals:** benzyl alcohol; 2-piperazin-1-ylethylamine
  - SARA 311/312 MSDS distribution - chemical inventory - hazard identification:**  
benzyl alcohol: Immediate (acute) health hazard, Delayed (chronic) health hazard; 2-piperazin-1-ylethylamine: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard
- State regulations** :
- Connecticut Carcinogen Reporting:** None of the components are listed.
  - Connecticut Hazardous Material Survey:** None of the components are listed.
  - Florida substances:** None of the components are listed.
  - Illinois Chemical Safety Act:** None of the components are listed.
  - Illinois Toxic Substances Disclosure to Employee Act:** None of the components are listed.
  - Louisiana Reporting:** None of the components are listed.
  - Louisiana Spill:** None of the components are listed.
  - Massachusetts Spill:** None of the components are listed.
  - Massachusetts Substances:** The following components are listed: BENZYL ALCOHOL; 1-(2-AMINOETHYL)-PIPERAZINE
  - Michigan Critical Material:** None of the components are listed.
  - Minnesota Hazardous Substances:** None of the components are listed.
  - New Jersey Hazardous Substances:** The following components are listed: PERFUMERY PRODUCTS, WITH FLAMMABLE SOLVENT; N-AMINOETHYLPIPERAZINE
  - New Jersey Spill:** None of the components are listed.
  - New Jersey Toxic Catastrophe Prevention Act:** None of the components are listed.
  - New York Acutely Hazardous Substances:** None of the components are listed.
  - New York Toxic Chemical Release Reporting:** None of the components are listed.
  - Pennsylvania RTK Hazardous Substances:** The following components are listed: BENZENEMETHANOL; 1-PIPERAZINEEETHANAMINE
  - Rhode Island Hazardous Substances:** None of the components are listed.

- United States inventory (TSCA 8b)** : All components are listed or exempted.

## 16 . Other information

**Hazardous Material Information System (U.S.A.)** :

Health	*	3
Flammability		1
Physical hazards		0
Personal Protection Equipment		D

## 16 . Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**Date of printing** : 08.10.2008.  
**Date of issue** : 08.10.2008.  
**Date of previous issue** : No previous validation.  
**Version** : 1

✔ Indicates information that has changed from previously issued version.

### Notice to reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikacorp.com](http://www.sikacorp.com) or 201-933-8800.