



# Sika Corporation

## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Material Identification

Product Name: SIKAFLOOR 207 PART H  
Product Use: Paint product.  
Print date: 18/Aug/2008  
Revision Date: 18/Aug/2008

#### Company Identification

Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Manufacturer's Phone: 1-201-933-8800

#### 24-Hour Medical Emergency Phone

CHEMTREC - In US: 1-800-424-9300; International: 703-527-3887

### 2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Common Name CAS-No.	Approx. Weight %	Chemical name
SUPPLIER TRADE SECRET	95 - 100	SUPPLIER TRADE SECRET

If this section is blank there are no hazardous components per OSHA guidelines.

### 3. HAZARDS IDENTIFICATION

#### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

#### Emergency Overview:

This section not in use.

**This product contains ingredients that may contribute to the following potential acute health effects:**

#### Inhalation Effects:

May cause Central Nervous System effects. May result in burning sensation of the mucous membranes.

#### Eye Contact:

Eye contact may cause blindness. Causes eye burns. Causes severe eye irritation

#### Skin Contact:

Causes burns.

#### Acute Ingestion:

Causes burns of the mouth, throat and stomach.

#### Other Effects:

None known

**This product contains ingredients that may contribute to the following potential chronic health effects:**

May cause eye damage and pain. May cause redness and blistering of skin. Possible sensitization. May result in asthma, bronchitis, difficulty breathing or wheezing.

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

#### **4. FIRST AID MEASURES**

**Inhalation:**

Move person to fresh air.

**Eye Contact:**

Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

**Skin Contact:**

Contact a physician to determine best course of action. Cover the affected area with a sterile dressing or clean sheeting and transport for medical care. Remove contaminated clothing. Wash skin with water, using soap if available.

**Ingestion:**

If swallowed, contact medical personnel immediately to determine best course of action.

**Medical conditions aggravated by exposure:** Any respiratory or skin condition.

#### **5. FIRE FIGHTING MEASURES**

Flash point (Fahrenheit):	225° F ( 107° C) TCC/PM
Lower explosive limit:	Not available. %
Upper explosive limit:	Not available. %
Autoignition temperature:	Not available. ° F ( ° C)
Sensitivity to impact:	No.
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

**Unusual fire and explosion hazards:**

None known.

**Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

**Fire fighting procedures:**

Use water spray to cool nearby containers and structures exposed to fire.

#### **6. ACCIDENTAL RELEASE MEASURES**

**Action to be taken if material is released or spilled:**

Avoid all personal contact.

#### **7. HANDLING AND STORAGE**

**Precautions to be taken in handling and storage:**

Keep container closed when not in use.

#### **8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS**

## Personal Protective Equipment

### Eye and face protection:

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

### Skin protection:

Gloves: Neoprene or other nonporous. Neoprene or plastic apron and protective clothing covering exposed skin areas.

### Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

### Ventilation

Required when spraying or applying in confined area.

## Exposure Guidelines

### OSHA Permissible Exposure Limits (PEL's)

### ACGIH Threshold Limit Value (TLV's)

If this section is blank, no information is available.

## 9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	Liquid
pH:	Not determined.
Vapor pressure:	Not determined. mmHG @ 68° F ( 20° C)
Vapor density (air = 1.0):	Not determined.
Boiling point:	Not available. ° F ( No information available° C)
Solubility in water:	Insoluble.
Coefficient of water/oil distribution:	Not determined.
Density (lbs per US gallon):	8.57
Specific Gravity:	1.03
Evaporation rate (butyl acetate = 1.0):	Not determined.

## 10. STABILITY AND REACTIVITY

Stability:	Stable
Conditions to Avoid:	None known.
Incompatibility:	None known.
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Aldehydes.

**Sensitivity to static discharge:** Sensitivity to static discharge is not expected.

## 11. TOXICOLOGICAL INFORMATION

**Mutagens:**

**Teratogens:**

**Carcinogens:**

If this section is blank, no information is available.

**12. ECOLOGICAL DATA**

Not available at this time.

**13. DISPOSAL CONSIDERATIONS**

Disposal should be made in accordance with federal, state and local regulations.

**14. TRANSPORTATION INFORMATION****U.S. Department of Transportation**

Proper Shipping Name: PAINT  
Hazard Class: 8  
UN ID Number: UN3066  
Packing Group: II

**U.S. Highway & Rail Shipments**

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

**International Air Transport Association:**

Proper Shipping Name: PAINT  
Hazard Class: 8  
UN ID Number: UN3066  
Packing Group: II

**International Maritime Organization:**

Proper Shipping Name: PAINT  
Hazard Class: 8  
Non-Bulk UN ID Number: UN3066  
Packing Group: II

**15. REGULATORY INFORMATION****U.S. FEDERAL REGULATIONS:****SARA 311/312 Hazard Class:**

Acute: Yes  
Chronic: Yes  
Flammability: No  
Reactivity: No  
Sudden Pressure: No

**U.S. STATE REGULATIONS:****Pennsylvania Right To Know:**

SUPPLIER TRADE SECRET

Trade Secret

**Rule 66 status of product**

Not photochemically reactive.

**INTERNATIONAL REGULATIONS - Chemical Inventories**

**TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

**16. OTHER INFORMATION**

**HMIS Codes**

<b>Health:</b>	3*
<b>Flammability:</b>	1
<b>Reactivity:</b>	1
<b>PPE:</b>	X - See Section 8 for Personal Protective Equipment (PPE).

**Abbreviations:**

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

**Disclaimer:**

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

**SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikacorp.com](http://www.sikacorp.com) or 201-933-8800.