



Material Safety Data Sheet

Sikafloor-29N Purcem, Part C

1. Product and company identification

Product name : Sikafloor-29N Purcem, Part C
Supplier : Sika Corporation, Operations
201 Polito Avenue
Lyndhurst, NJ 07071
www.sikacorp.com
Telephone no. : (201) 933 - 8800
Fax no. : (201) 804 - 1076
In case of emergency : CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887
Manufacturer : Sika Corporation, Operations
201 Polito Avenue
Lyndhurst, NJ 07071
www.sikacorp.com
Telephone no. : (201) 933 - 8800
Validation date : **13. June 2008.**
Print date : 13. June 2008.
Product type : Powder.

2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential acute health effects

Inhalation : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Ingestion : May be harmful if swallowed.
Skin : Alkaline. When product exposed to moisture, skin contact may produce burns or irritation.
Eyes : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.

Potential chronic health effects

Chronic effects : May cause sensitization by skin contact. Repeated inhalation of dust can produce varying degrees of respiratory irritation or lung damage.
Carcinogenicity : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.

See toxicological information (section 11)

3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Quartz (SiO ₂)	14808-60-7	60 - 100
Cement, portland, chemicals	65997-15-1	10 - 30

There are no ingredients or additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4 . First aid measures

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 . Fire-fighting measures

Flammability of the product : No specific fire or explosion hazard.

Extinguishing media

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous combustion products : Decomposition products may include the following materials:
metal oxide/oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Large spill : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Small spill : Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

Handling : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Expose controls/personal protection

Product name

Quartz (SiO₂)

Exposure limits

ACGIH TLV (United States, 1/2007). Notes: Respirable fraction; see Appendix C, paragraph C.

TWA: 0.025 mg/m³ 8 hour(s). Form: Respirable fraction

NIOSH REL (United States, 12/2001). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen

TWA: 0.05 mg/m³ 10 hour(s).

OSHA PEL 1989 (United States, 3/1989). Notes: as quartz

TWA: 0.1 mg/m³, (as quartz) 8 hour(s). Form: Respirable dust

OSHA PEL Z3 (United States, 9/2005).

TWA: 10 mg/m³ 8 hour(s). Form: Respirable

TWA: 30 mg/m³ 8 hour(s). Form: Total dust.

TWA: 250 mppcf 8 hour(s). Form: Respirable

Cement, portland, chemicals

ACGIH TLV (United States, 1/2007).

TWA: 10 mg/m³ 8 hour(s).

NIOSH REL (United States, 12/2001).

TWA: 5 mg/m³ 10 hour(s). Form: Respirable fraction

TWA: 10 mg/m³ 10 hour(s). Form: Total

OSHA PEL (United States, 11/2006).

TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction

TWA: 15 mg/m³ 8 hour(s). Form: Total dust

OSHA PEL 1989 (United States, 3/1989).

TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction

TWA: 10 mg/m³ 8 hour(s). Form: Total dust

Engineering measures

- : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

- : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If operating conditions cause high dust concentrations to be produced, use dust goggles.

Skin

- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

9 . Physical and chemical properties

Flash point	: Closed cup: Not applicable.
Color	: White.
Odor	: Odorless.
pH	: >12 [Conc. (% w/w): 50%]
Solubility	: Insoluble in the following materials: cold water.

10 . Stability and reactivity

Stability	: The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	: Avoid exposure - obtain special instructions before use.
Materials to avoid	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 . Toxicological information

Acute toxicity

Conclusion/Summary : Not available.

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Quartz (SiO ₂)	A2	1	-	+	Proven.	-

12 . Ecological information

Environmental effects : No known significant effects or critical hazards.

13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Additional information
DOT Classification	Not regulated.		-	-	-
TDG Classification	Not regulated.		-	-	-
ADR/RID Class	Not regulated.		-	-	-

14 . Transport information

IMDG Class	Not regulated.	-	-	-
IATA-DGR Class	Not regulated.	-	-	-

PG* : Packing group

15 . Regulatory information

- U.S. Federal regulations** : **United States inventory (TSCA 8b)**: At least one component is not listed.
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: Cement, portland, chemicals; Quartz (SiO₂)
SARA 311/312 MSDS distribution - chemical inventory - hazard identification:
Cement, portland, chemicals: Immediate (acute) health hazard; Quartz (SiO₂):
Immediate (acute) health hazard, Delayed (chronic) health hazard
- State regulations** : **Connecticut Carcinogen Reporting**: None of the components are listed.
Connecticut Hazardous Material Survey: None of the components are listed.
Florida substances: None of the components are listed.
Illinois Chemical Safety Act: None of the components are listed.
Illinois Toxic Substances Disclosure to Employee Act: None of the components are listed.
Louisiana Reporting: None of the components are listed.
Louisiana Spill: None of the components are listed.
Massachusetts Spill: None of the components are listed.
Massachusetts Substances: The following components are listed: SILICA, CRYSTALLINE, QUARTZ;PORTLAND CEMENT
Michigan Critical Material: None of the components are listed.
Minnesota Hazardous Substances: None of the components are listed.
New Jersey Hazardous Substances: The following components are listed: SILICA, QUARTZ;SILICATE, PORTLAND CEMENT
New Jersey Spill: None of the components are listed.
New Jersey Toxic Catastrophe Prevention Act: None of the components are listed.
New York Acutely Hazardous Substances: None of the components are listed.
New York Toxic Chemical Release Reporting: None of the components are listed.
Pennsylvania RTK Hazardous Substances: The following components are listed: QUARTZ (SiO₂);CEMENT, PORTLAND, CHEMICALS
Rhode Island Hazardous Substances: None of the components are listed.

California Prop. 65**WARNING**: This product contains a chemical known to the State of California to cause cancer.

<u>Ingredient name</u>	<u>Cancer</u>	<u>Reproductive</u>	<u>No significant risk level</u>	<u>Maximum acceptable dosage level</u>
Quartz (SiO ₂)	Yes.	No.	No.	No.

- United States inventory (TSCA 8b)** : **United States inventory (TSCA 8b)**: At least one component is not listed.

16 . Other information

Hazardous Material Information System (U.S.A.) :

Health	*	2
Flammability		0
Physical hazards		0
Personal Protection Equipment		E

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Date of printing : 13.06.2008.
 Date of issue : 13.06.2008.
 Date of previous issue : No previous validation.
 Version : 1

☑ Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.