



Sika Corporation

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Material Identification

Product Name: SIKAFLOOR 310 PART H
Product Use: Paint product.
Print date: 05/Sep/2008
Revision Date: 03/Sep/2008

Company Identification

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Manufacturer's Phone: 1-201-933-8800

24-Hour Medical Emergency Phone:

CHEMTREC - In US: 1-800-424-9300; International: 703-527-3887

2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| Common Name CAS-No. | Approx. Weight % | Chemical name |
|---------------------------------|---------------------|----------------------|
| ACETONE 67-64-1 | 60 - 90 | ACETONE |
| PROPYLENE CARBONATE 108-32-7 | 1 - 5 | Propylene carbonate |
| PROPRIETARY ADDITIVE | 15 - 25 | PROPRIETARY ADDITIVE |
| PLASTICIZER 131-11-3 | 1 - 5 | DIMETHYL PHTHALATE |
| | | |

If this section is blank there are no hazardous components per OSHA guidelines.

3. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Emergency Overview:

This section not in use.

This product contains ingredients that may contribute to the following potential acute health effects:

Inhalation Effects:

Vapors (generated by contact with moisture/water) irritate the respiratory tract.

Eye Contact:

Contact with liquid causes severe eye irritation.

Skin Contact:

Contact with liquid causes severe skin irritation.

Acute Ingestion:

Harmful if swallowed.

Other Effects:

None known

This product contains ingredients that may contribute to the following potential chronic health effects:

May cause eye damage and pain. Prolonged skin contact with very large amounts may cause drowsiness.

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

4. FIRST AID MEASURES

Inhalation:

If affected by inhalation, move victim to fresh air. If symptoms persist, seek medical attention. Contact a physician immediately. If symptoms develop, seek medical attention. Move person to fresh air.

Eye Contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

Skin Contact:

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean contaminated shoes. Flush with large amounts of water; use soap if available. Remove contaminated clothing and launder before reuse. Wash with soap and water.

Ingestion:

If swallowed, get medical attention immediately. Get immediate medical attention. If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person. If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person.

Medical conditions aggravated by exposure: Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

| | |
|----------------------------------|--|
| Flash point (Fahrenheit): | 115° F (46° C) TCC/PM |
| Lower explosive limit: | 1.21 % |
| Upper explosive limit: | 5.35 % |
| Autoignition temperature: | Not available. ° F (° C) |
| Sensitivity to impact: | No. |
| Sensitivity to static discharge: | Can be sensitive to static discharge hazards. Please see bonding and grounding information in Section 7. |
| Hazardous combustion products: | See Section 10. |

Unusual fire and explosion hazards:

None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Use water spray to cool nearby containers and structures exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate area. Avoid breathing of vapors. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 5, "Unusual Fire and Explosion Hazards", for proper container and storage procedures. Remove sources of ignition. Remove with inert absorbent and non sparking tools. Avoid contact with eyes.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep away from heat, sparks, and flames. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Avoid contact with eyes. Wear chemical goggles if there is the possibility of contact or splashing in the eye.

Skin protection:

Appropriate chemical resistant gloves should be worn. To prevent skin contact wear protective clothing covering all exposed areas.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Required when spraying or applying in confined area. Ventilation equipment should be explosion proof.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

| Common Name CAS-No. | Approx. Weight % | TWA (final) | Ceilings limits (final) | Skin designations |
|-------------------------|---------------------|---------------------------|-------------------------|-------------------|
| PLASTICIZER 131-11-3 | 1 - 5 | 5 mg/m ³ | | |
| PROPRIETARY ADDITIVE | 1 - 5 | 0.1 mg/m ³ Sn_ | | |

ACGIH Threshold Limit Value (TLV's)

| Common Name CAS-No. | Approx. Weight % | TWA | STEL | Ceiling limits | Skin designations |
|-------------------------|---------------------|---------------------|------|----------------|-------------------|
| PLASTICIZER 131-11-3 | 1 - 5 | 5 mg/m ³ | | | |

| Common Name CAS-No. | Approx. Weight % | TWA | STEL | Ceiling limits | Skin designations |
|------------------------|---------------------|---------------------------|---------------------------|----------------|---------------------------------------|
| PROPRIETARY ADDITIVE | 1 - 5 | 0.1 mg/m ³ Sn_ | 0.2 mg/m ³ Sn_ | | Sn_ Can be absorbed through the skin. |

If this section is blank, no information is available.

9. PHYSICAL PROPERTIES

| | |
|---|-------------------------------|
| Odor: | Normal for this product type. |
| Physical State: | Liquid |
| pH: | Not determined. |
| Vapor pressure: | 9.75 mmHG @ 68° F (20° C) |
| Vapor density (air = 1.0): | 6.7 |
| Boiling point: | 408° F (209° C) |
| Solubility in water: | Slightly Soluble |
| Coefficient of water/oil distribution: | Not determined. |
| Density (lbs per US gallon): | 8.74 |
| Specific Gravity: | 1.05 |
| Evaporation rate (butyl acetate = 1.0): | Not determined. |

10. STABILITY AND REACTIVITY

| | |
|-----------------------------------|-------------------------------------|
| Stability: | Stable |
| Conditions to Avoid: | None known. |
| Incompatibility: | None known. |
| Hazardous Polymerization: | None anticipated. |
| Hazardous Decomposition Products: | Carbon monoxide and carbon dioxide. |

Sensitivity to static discharge: Can be sensitive to static discharge hazards. Please see bonding and grounding information in Section 7.

11. TOXICOLOGICAL INFORMATION

Mutagens:

Teratogens:

Carcinogens:

If this section is blank, no information is available.

12. ECOLOGICAL DATA

Not available at this time.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

Proper Shipping Name: PAINT
 Hazard Class: COMBUSTIBLE LIQUID
 UN ID Number: UN1263
 Packing Group: III

49 CFR Hazardous Material Regulations Parts 100-180

The supplier will apply the combustible liquid exception in 49 CFR 173.150(f), limited quantity or "does not sustain combustion" exceptions and consumer commodity rules, when authorized. Please check 49 CFR Parts 100-180 to determine if the use of these exceptions applies to your shipments when re-shipping our products.

International Air Transport Association:

Proper Shipping Name: PAINT
 Hazard Class: 3
 UN ID Number: UN1263
 Packing Group: III

International Maritime Organization:

Proper Shipping Name: PAINT
 Hazard Class: 3
 Non-Bulk UN ID Number: UN1263
 Packing Group: III

15. REGULATORY INFORMATION**U.S. FEDERAL REGULATIONS:**

| Common Name CAS-No. | Approx. Weight % | SARA 302 | SARA 313 | CERCLA RQ in lbs. |
|-------------------------|---------------------|----------|--------------------|-------------------|
| PLASTICIZER 131-11-3 | 1 - 5 | | DIMETHYL PHTHALATE | 5000 |

SARA 311/312 Hazard Class:

Acute: Yes
 Chronic: Yes
 Flammability: Yes
 Reactivity: No
 Sudden Pressure: No

U.S. STATE REGULATIONS:**Pennsylvania Right To Know:**

PROPYLENE CARBONATE 108-32-7
 PLASTICIZER 131-11-3
 PROPRIETARY ADDITIVE Trade Secret
 PROPRIETARY ADDITIVE Trade Secret
 ETHER 88917-22-0

Rule 66 status of product

Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories**TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

16. OTHER INFORMATION

HMIS Codes

| | |
|---------------|----|
| Health: | 2* |
| Flammability: | 2 |
| Reactivity: | 0 |
| PPE: | C |

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.