



MATERIAL SAFETY DATA SHEET

Sikafloor 81 EpoCem - Part C

HMIS

HEALTH	*2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	C

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Canada Inc.
601, Avenue Delmar
Pointe Claire, QC H9R 4A9 Canada

Company Contact: Steve Gosselin
Telephone Number: 514-697-2610

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CANUTEC: 613-996-6666

Issue Date: 01/23/2006

Product Name: Sikafloor 81 EpoCem - Part C
CAS Number: Not Established
MSDS Number: 3805

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
CALCIUM SILICATE	1344-95-2	
MAGNESIUM OXIDE	1309-48-4	
SILICA, QUARTZ	14808-60-7	

3. Hazards Identification

Eye Hazards

May cause eye irritation, burns. May cause cornea inflammation.

Skin Hazards

Product becomes alkaline when exposed to moisture. May cause skin irritation. Prolonged and/or repeated skin contact may cause an allergic reaction/sensitization.

Ingestion Hazards

May be harmful if swallowed.

Inhalation Hazards

May cause respiratory tract irritation. Breathing dust may cause nose, throat or lung irritation. Respirable

MATERIAL SAFETY DATA SHEET

Sikafloor 81 EpoCem - Part C

3. Hazards Identification - Continued

Inhalation Hazards - Continued

crystalline silica can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration, seek medical attention.

5. Fire Fighting Measures

Flash Point: N/A °F

Fire And Explosion Hazards

None known

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Avoid release to the environment. Using appropriate personal protective equipment (PPE), shovel material into waste containers taking care to minimize dust. Dampen if necessary to control dust. Vacuum clean dust with equipment fitted with High Efficiency Particulate Air (HEPA) filters.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store in a cool, dry, well ventilated area. Keep containers tightly closed.

8. Exposure Controls/Personal Protection

Engineering Controls

Use of a system of local and/or general exhaust is recommended to keep employee below applicable exposure limits. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure (Long sleeve shirt and long pants). Launder before reuse.

MATERIAL SAFETY DATA SHEET

Sikafloor 81 EpoCem - Part C

8. Exposure Controls/Personal Protection - Continued

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Ingredient(s) - Exposure Limits

CALCIUM SILICATE

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 15 mg/m³

OSHA PEL-TWA 5 mg/m³

MAGNESIUM OXIDE

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 15 mg/m³

SILICA, QUARTZ

ACGIH TLV-TWA 0.1 mg/m³ (Notice of Intended Change)

ACGIH TLV-TWA 0.05 mg/m³ (Proposed)

OSHA PEL-TWA 30/%SiO₂+2 mg/m³

OSHA PEL-TWA 10/%SiO₂+2 mg/m³

OSHA PEL-TWA 250/%SiO+5 mppcf

9. Physical And Chemical Properties

Appearance

White powder

Odor

Odorless

Chemical Type: Mixture

Physical State: Solid

Specific Gravity: 2.8

Solubility: <1% in water

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR

Conditions To Avoid (Stability)

None known

Incompatible Materials

Water

Hazardous Decomposition Products

Calcium Hydroxide at water contact

Conditions To Avoid (Polymerization)

None known

11. Toxicological Information

Ingredient(s) - Carcinogenicity

SILICA, QUARTZ

NTP - Listed On The National Toxicology Program

Listed In The IARC Monographs

MATERIAL SAFETY DATA SHEET

Sikafloor 81 EpoCem - Part C

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Proper Shipping Name

Not Regulated by the US DOT

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard
Chronic Health Hazard

State Regulations

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

Ingredient(s) - State Regulations

CALCIUM SILICATE
Pennsylvania - Workplace Hazard
MAGNESIUM OXIDE
New Jersey - Workplace Hazard
Pennsylvania - Workplace Hazard
Massachusetts - Hazardous Substance
New York City - Hazardous Substance
SILICA, QUARTZ
New Jersey - Workplace Hazard
Pennsylvania - Workplace Hazard
California - Proposition 65
Massachusetts - Hazardous Substance

16. Other Information

HMIS Rating

Health: *2

Fire: 0

Reactivity: 0

PPE: C

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

MATERIAL SAFETY DATA SHEET

Sikafloor 81 EpoCem - Part C

Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000