

AZIRADINE

CROSSLINKER

Technical Data Sheet

DESCRIPTION:

An Aziradine crosslinker for use in Water based Urethane Gym Finishes. This catalyst must be used to achieve the maximum physical properties.

ADVANTAGES:

- Excellent rubber burn resistance
- Increased Chemical resistance

PACKAGING:

This product is packaged in 2 ounce bottles.

DIRECTIONS:

THIS PRODUCT IS DESIGNED TO BE USED AS IS THEREFORE THINNING OR REDUCING WITH SOLVENTS IS NOT RECOMMENDED

Do not use water based Urethane finishes to seal newly installed floors or sanded to bare wood, use **WP-3 Acrylic sealer**.

Previously coated floors

This catalyst is pre-portioned for error-free job site mixing. Two ounces of catalyst per gallon of Water Base finish are needed to obtain maximum physical properties. Prior to application, pour the catalyst into the gallon container. Mix by gently inverting 6 - 10 times. Do not shake vigorously as this will cause foaming. Catalyze each coat prior to application.

POTLIFE:

The Finish/ crosslinker mixture is active for approximately 24 hours.

CAUTION:

- 1) Avoid prolonged breathing of vapors or mist. Causes lung irritation, eye burns and skin irritation. May cause allergic respiratory reaction and skin sensitization. Harmful if inhaled. Do not breathe dust, vapor or spray mist
- 2) Open doors and windows to ensure fresh air entry during application and drying. If necessary wear respiratory equipment (NIOSH/ MSHA TC-23C or equivalent).
- 3) Avoid skin contact, eye contact, or clothes.

GENERAL PROPERTIES:

GENERAL PROPERTIES:		ASTM
Color	Straw	-----
Weight/Gallon	8.2 - 8.4 Lbs.	D1475
Flash Point	200°F+	D56

FIRST AID:

- 1) Skin contact wash with soap and water.
- 2) Eye contact: flush with water for 15 minutes and get medical attention.
- 3) If swallowed do not induce vomiting, get medical attention immediately.
- 4) If experience watering eyes, headaches, dizziness, nose or throat irritation; increase the flow of fresh air, or leave the area.

NOTICE:

- 1) Long-term overexposure to solvents has been associated with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DISPOSAL:

All label warnings must be observed until the container has been commercially cleaned, reconditioned, or disposed of in accordance with local government regulations.

Refer to Material Safety Data Sheet for further safety and handling information.

For Emergency Medical Information call 1-888-345-5732

KEEP OUT OF REACH OF CHILDREN

© Copyright 2007 Valspar Corporation. All rights reserved.
TDS-Aziridine | Rev 03/15/07 ly

WARRANTY STATEMENT | IMPORTANT: The data on this sheet represent typical values obtained by the methods indicated. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. Unless Valspar agrees otherwise in writing, **VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Unless Valspar agrees otherwise in writing, Valspar's only obligation for any defect in this product under any warranty that Valspar provides or under any other legal theory will be to replace the defective product, or to refund its purchase price, at Valspar's option. Revision E: 12 FEB 2002