

- 1) **Dust mop every day with a clean untreated dust mop or dust mop treated with a water based neutral gym floor cleaner. Follow label instructions about usage.**
 - a. Several dust moppings per day may be required during seasons of heavy use. To maintain a non-slip surface it is necessary to remove soil (grit) and to remove any films on the surface. Dust mops should be cleaned regularly.
 - b. Dust mops should be cleaned regularly.
 - c. Damp mop floor with a neutral cleaner (2-3 oz./gal) making sure not to flood floor in process. Always use a cleaning product that will not leave any film on surface, which can cause a slippery surface.
- 2) **All entrances should have walk off mats to lesson amount of soil being deposited on floor. Mats should be cleaned often.**
- 3) **HVAC filters should be changed or cleaned often to prevent an excessive amount of dust and lint being deposited on floor.**
- 4) **Always remember, good maintenance will postpone the need of recoating.**
- 5) **High speed burnishing – water based finishes:**
 - a. Check with manufacturer to see if Water Based Finishes may be burnished.
 - b. Gloss can be restored with use of high speed burnishers.
 - c. (Propane and conventional machines) 1,000 rpm and higher using a “hogs hair” composite pad. Propane burnishers will restore the finish to a higher gloss. Do not use any burnishing liquids, burnish dry. Before burnishing remove all soil and any gum or tar from floor. Scrub and damp mop with Neutral Cleaner, rinse and let dry thoroughly. Black marks can be removed prior with Waterless Cleaner on a rag or towel.